

WORLD
WIDE
INNOVATION


JDM CT 4/6 the innovative space miracle

FRUCT  **MAT**

BY ASCO DRINK MACHINES



A NEW DIMENSION in design and functionality



- No space left at the counter or buffet? Problem solved with our JDM CT- the countertop dispenser for 4 oder 6 drinks plus cooled water and (optional) additional CO² water with drink carbonation function!
- NEW – ALL MODELS ALSO AS HOT&COLD VERSION! = ALL DRINKS CHILLED OR WITH PRESELECTION HOT (such as: NATURAL TEA, ISOTONIC DRINKS, ETC.)
- Height of dispensing area model JDM CT-S = 180 mm; model JDM CT-L = 300 mm plus cup/glass-shelf adjustable with folding mechanism in 4 different heights for cups/glasses for carafes and sports bottles (fitness center).
- Innovative, modern and timeless design with highest material and finishing quality as well as simple and logical operation. Unbelievable clean product exit und fully automatic cleaning.
- Fully flexible mounting! The whole mechanism disappears into the base cabinet or the existing counter. (in SPLIT-version extremely small for external cooling). The drink cartons in different sizes are also hidden in base cabinet – this allows simple refilling and plenty of space remains on the counter or buffet!

THE SPACE-SAVING MIRACLE

No annoying boxes on your counter and up to 6 drinks (also hot&cold) plus water plus CO² (Option)! Attractively styled, smart and timeless, with vandal-proof stainless steel selection buttons and integrated customer info display. The placement of the cup is highlighted with LED lighting.



standard delivery without base cabinet



Model JDM CT-L DESIGN
Frontdisplay by request with customer-specific logo or design of drink brand, mit LED-lighting (not for CO²-Option)

Less space and perfect design!
with drip tray and on demand with additional outlet



Simple operation – very clean drinks exit with fully automatic cleaning





NEW – ALL MODELS CT 4 and 6 also as hot & cold version

JDM CT models: ambient & still (cold) // still (cold) & Co2 // ambient & HOT // still (cold) & HOT

TECHNICAL DATA	JDM CT-S4	JDM CT-S6	JDM CT-L4	JDM CT-L6	JDM CT-SPLIT-4	JDM CT-SPLIT-6
Selection+drink exit panel+ column	S4	S6	L4	L6	S4 / L4	S6 / L6
width	210 mm	210 mm	210 mm	210 mm	210 mm	210 mm
height	410 mm	410 mm	530 mm	530 mm	410 / 530 mm	410 / 530 mm
depth	250 mm	250 mm	250 mm	250 mm	250 mm	250 mm
exit-height	max 180 mm	max 180 mm	140 - max 300 mm	140 - max 300 mm	180 mm / 300 mm	180 mm / 300 mm
weight	8 kg	8 kg	9 kg	9 kg	8 / 9 kg	8 / 9 kg
Technic box						
width	260 mm	260 mm	260 mm	260 mm	410 mm	580 mm h=125 mm
height	350 mm	350 mm	350 mm	350 mm	125 mm	210 mm b=410 mm
depth	440 mm	440 mm	440 mm	440 mm	200 mm	200 mm
weight	max 40 kg	max 40 kg	max 40 kg	max 40 kg	10 kg	10 / 12 kg
distance technic-box to selection panel	max 5 m	max 5 m	max 5 m	max 5 m	max 5 m	max 5 m
working pressure	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar
current	230 V/ 50-60 Hz	230 V/ 50-60 Hz	230 V/ 50-60 Hz	230 V/ 50-60 Hz	230 V/ 50-60 Hz	230 V/ 50-60 Hz
max power ambient	30 W	30 W	30 W	30 W	30 W	30 W
max power still cold	365 W	365 W	365 W	365 W	extern	extern
max power Co2 cold	415 W	415 W	415 W	415 W	extern	extern
max power HOT & COLD	2700 W	2700 W	2700 W	2700 W	extern	extern
cooling capacity (dT = 10°C)	30 ltr/h	30 ltr/h	30 ltr/h	30 ltr/h	extern	extern
drink temperature still / Co2	5°C - ambient	5°C - ambient	5°C - ambient	5°C - ambient	extern	extern
drink temperature HOT	5°C - 85°C	5°C - 85°C	5°C - 85°C	5°C - 85°C	extern	extern
FSS ¹	YES	YES	YES	YES	YES	YES
MidMix II System	YES	YES	YES	YES	YES	YES
flowmeter	YES	YES	YES	YES	YES	YES
drink size direct selection	100-500 ml / PULSE	100-500 ml / PULSE	100-500 ml / PULSE	100-500 ml / PULSE	100-500 ml / PULSE	100-500 ml / PULSE
drink size preselection EXTRA/CARAFE	up to max 2000 ml	up to max 2000 ml	up to max 2000 ml	up to max 2000 ml	up to max 2000 ml	up to max 2000 ml
mixing ratio concentrates	1 + 4 bis 1 + 49	1 + 4 bis 1 + 49	1 + 4 bis 1 + 49	1 + 4 bis 1 + 49	1 + 4 bis 1 + 49	1 + 4 bis 1 + 49
direct selections	6	8	6	8	6 / 8	6 / 8
ESI ² drink labels	YES	YES	YES	YES	YES	YES
column LED illuminated	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
drink exit LED illuminated	YES	YES	YES	YES	YES	YES
drinks/flavours	4	6	4	6	4 / 6	4 / 6
payment options	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
bookkeeping	YES	YES	YES	YES	YES	YES
payment protocols	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE
ETCS ³	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
SIV ⁴ syrup injection valve	YES	YES	YES	YES	YES	YES
syrup empty message	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
water gallon pump system	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
desinfection period control	YES	YES	YES	YES	YES	YES
automatic desinfection	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL

1. FSS >> Flood safety system with extra safety valve (water inlet)

2. ESI > (Easy Slide In) Product label slide-in technology for very fast and simple label replacement

3. ETCS > (Easy Tube Change System) Faster hose change for highest hygiene demands

4. SIV > (Syrup Injection Valve) Drink concentrate injection valve for perfect mixing results



FRUCTOMAT
BY ASCO DRINK MACHINES

ASCO DRINK MACHINES Produktions- & HandelsgmbH
Steyrer Straße 80, A-4470 Enns, T. +43 (0) 7223 86197-0
www.fructomat.com, www.asco.at